

FAKTABLAD



SUNBRELLA LINEN

Dynväv

EGENSKAPER	VÄRDEN		ENHET	STANDARDER
	VARP	VÄFT		

ALLMÄNNA EGENSKAPER

Sammansättning	100% Sunbrella solution dyed acrylic			
Slutbehandling	Stain-resistant treatment: exclusive Glen Raven formulation. Does not contain PFOS (perfluorooctanyl sulphonate)			
Bindning	irregular braiding			ISO 7211-1
Vikt	275		g/m ²	ISO 2286-1
Tygbredd	137		cm	EN 1773

TYGETS SLITSTYRKA

Resistens mot eld	class 1			NF P 92 503
Oljeavvisande behandling	5			class /8 ISO 14419
Brottstyrk	160	90	daN	ISO 13934-1
Rivhållfasthet	> 13.5	12	daN	ISO 13937-1
Brottöjning	33	27	%	ISO 13934-1
Schmerber-test	100			mm ISO 811
Spray-test	5			class /5 ISO 4920
Stabilité au lavage (40 °C°)	-1	-0.5	%	ISO 5077
Slitage (Martindale)	15.000			Nb cycles ISO 12947-2
Luftgenomtränglighet	130			l/m ² /s ISO 9237
Sömstyrka	48	33	daN	ISO 13935-1



FÄRGERS BESTÄNDIGHET

Färgers UV-beständighet	7/8	class /8	ISO 105 B02
Färgers väderbeständighet	7/8	class /8	ISO 105 B04
Färgers torrfröttering	5	class /5	ISO 105X12
Färgers våtfröttering	5	class /5	ISO 105X12
Färgers au lavage (40 °C°)	5	class /5	ISO 105 C06

ANVÄNDNING

Skärlängd	50	lm	
Rekommenderad användning	Cushion, parasol and upholstery		
Garanti	5	År	

The values for this product may have a variation of +/-5%.
Stitch test carried out with 32pts/100mm, a 110 needle, and a 100% Pes 74 tex thread.

Dickson - Constant

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France
Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com